



Model: LP503040		Overcharge Detection Voltage(V)	4.28±0.05
Min. Capacity/最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)		Overdischarge Detection Voltage(V)	3.0±0.1
530		Limited to Max loading current 仅用于最大的负载电流	constant (A) 持续 0.5 (A)
Typical Capacity/典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)		Customer required Max loading current 客户要求最大的负载电流	constant (A) 持续 (A)
560		Battery protection Related Value: (相关的电池保护值)	
Nominal Voltage/标称电压 (V)		3.7	
Internal impedance/内阻 (≤) (mΩ, AC 1KHZ)		250	
Ambient Conditions (环境温度)		Charge Temp./充电温度 (°C)	0~45
Discharge Temp./放电温度 (°C)		Humidity/(湿度)	-20~60 65±20%

EEMB BATTERY		Drawn:	Hexin	Revise No.:	E4-2009
Title	LP503040-PCM-LD	Checked 1:	Huangqinhui	Projection:	
File NO.	A10610	Checked 2:		Page:	1/1
		Approved:		Scale:	1:2
		Draw Date:	2014/12/03	Unit:	mm

Remark(备注):
1. No scratch, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
2. Rohns compliant(严格按照ROHS要求生产).