



Model:	ZLP7068130N	Overcharge Detection Voltage (V)	4.28±0.05	
	Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C)	4700	Overdischarge Detection Voltage (V)	3.0±0.1
Battery pack specification (电池组规格)	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C)	5000	Battery protection Related Value: (相关的电池保护值) Overcharge Detection Voltage (V) 过充保护电压 (V) Overdischarge Detection Voltage (V) 过放保护电压 (V) Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 (A) Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 (A) 持续 10 (A) 持续 5 (A) 持续 10 (A) 持续 5 (A)	
	Nominal Voltage 标称电压 (V)	25.9		
Internal impedance 内阻 (≦) (m AC 1KHz)	350			
Charge Temp. 充电温度 (°C)	0~45			
Ambient Conditions (环境温度)	Discharge Temp. 放电温度 (°C)	-20~55	If actual application loading current is bigger than EEMB suggested rate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用请列对PCM的设计至关重要)	
	Humidity (湿度)	65±20%		

		Drawn:	YanF	Revise No.:	E4-2009
Title	ZLP7068130N-PCM-LD	Group:	Group 19	Projection:	
File NO.	A17948	Approved1:		Page:	1/1
		Approved2:		Scale:	1 : 4
		Draw Date:	2019/12/09	Unit:	mm

Remark(备注):
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell/电池表面无划痕、变形、污点及漏液等现象).
 2. RoHS compliant(严格按照ROHS要求生产).