

PCB Layout Diagram  
Top View

NOTE:

1, Material:

- a. Housing: LCP UL94V-0
- Contact: Phosphor Bronze
- (Surface Plating: Sn=100u"~120u")
- See Ordering Information

2, Electric:

- a. Contact Resistance: 30 Milliohms Max
- b. Insulation Resistance: 1000 MEGA OHMS Min
- c. Dielectric Voltage: 500V AC One Sea Level
- d. Operating Temperature: -55° To 105°

Order code:

BT — M — SN — R — CR2032I  
 ① — ② — ③ — ④ — ⑤

- ① BT: Coin Cell Holders
- ② Appearance for the product
- M: SMT TYPE
- ③ Contact Plating


- SN: Tin
- G0: Gold flash
- G1: 3U" Gold
- G2: 5U" Gold
- G3: 10U" Gold
- G4: 15U" Gold
- G5: 30U" Gold

- ④ Packing method
- A: Tray packing
- R: Tape & reel packing

- ⑤ Product number
- CR2032I

Unless Otherwise specified tolerance  
 X. ±0.35 X.XX: ±0.20  
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm  
 DRAW Mo Guo Xuan DATE 03/14/2019  
 CHECK BobYang DATE 03/14/2019



**Antenk**® ANTENK ELECTRONICS CO., LTD  
[Http://www.antenk.com](http://www.antenk.com)  
 E-mail: sales@antenk.com

TITLE: Coin Cell Holders For CR2032

DRAWING NO: BT-M-SN-R-CR2032I

PRODUCT NO: BT-M-SN-R-CR2032I

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		