


## **High Temperature Capacitors**

85°C

- High temperature tolerant (-25 to  $+85^{\circ}$ C) and highly reliable.
- Ideal for backing up of controls, electronic rice cooking jars, home bakeries and the like.



High temperature Miniaturized


DH

 $\mathsf{DX}$ DB

## Specifications

Specifications							
Item	Performance						
Category temperature range (°C)	-25 to +85						
Tolerance at rated capacitance (%)	-20 to +80						
Internal resistance	Rated capacitance (F)	0.047	0.1	0.22	0.47	0.68	1
at 1 kHz	Internal resistance (Ω Max.)	300	200	120	50	50	30
Characteristics at high and low temperature	Percentage of capacitance change  Internal resistance						
Endurance (85°C)	Test time Percentage of capacitance change	1000 hours  Within ±30% of the initial measured value					
Endurance (65 6)	Internal resistance	Less than four times of the initial specified value					
Shelf life (85°C)	Test time: 1000 hours; Same as endurance.						
Applicable standards	Conforms to JIS C5160-1 2009 (IEC 62391-1 2006)						

## **Outline Drawing**



Part numbering system (example : 5.5V0.1F)								
DH	_	5R5	D	104	Т			
Series code		Max.operating voltage		Rated capacitance				

symbol

symbol

Part number is refer to following table.

Series code

## Standard Ratings

Max. operating voltage (V)	Rated capacitance (F)	ELNA Parts No.	φD×L (mm)
5.5	0.047	DH-5R5D473T	13.5×9.5
5.5	0.1	DH-5R5D104T	13.5×9.5
5.5	0.22	DH-5R5D224T	13.5×9.5
5.5	0.47	DH-5R5D474T	21.5×9.5
5.5	0.68	DH-5R5D684T	21.5×9.5
5.5	1	DH-5R5D105T	21.5×9.5