

Heatshrink tube
(热缩管)

Wire引线(+):Red红, UL1007 AWG24
Wire引线(-):Black黑, UL1007 AWG24

Blue PVC with date code
(包蓝色PVC 表面喷码)

HR14505

Insulation mat
(绝缘垫)

Cell(电芯):ER26500
EEMB PVC with date code
(包EEMB PVC 表面喷码)


Heatshrink tube(热缩管)

Connected
Nickel strip
(连接镍带)

Insulation mat
(绝缘垫)

Blue PVC
(包蓝色PVC)

T Top(T头)



Circuit diagram

50.0±3.0
Tinned 3.0±0.5

53.5Max

41.5Max

∅26.50±0.5

Remark (备注):

1. Pack:3.6V 3.6V 9000mAh,With wires,EEMB PVC.
(Fix horizontal wire by lead PVC tube and then cover the whole battery with erect PVC tube)
电池包:3.6V 9000mAh. 带输出引线, 包EEMB PVC.
(先用竖套PVC固定引线, 再用横套)
2. RoHS Compliant.
严格按照RoHS要求生产.



Title ER26500-HR14505-LD		Drawn:	YanF	Revise No.:	E4-2009
		Group:	Group19	Projection:	
		Approved1:		Page:	1/1
File NO.	A17360	Approved2:		Scale:	1 : 1
		Draw Date:	2019/07/17	Unit:	mm