

Features

- ◆ Very compact metal cased power supply
- ◆ Universal input AC input,full range
- ◆ Natural air cool
- ◆ Screw terminal block
- ◆ 2 years product warranty
- ◆ Protection: short-circuit,overload,overcurrent and over heat



12V 120W Normal Single output

Specifications

Output	DC Voltage (V)	12V				
	Voltage Range	11.40-13.20V				
	Rated Current (A)	10A				
	Current Range (A)	0 - 10A				
	Rated Power (W)	120W				
	Ripple & Noise (Mvp-p)	120mVP-P				
	voltage accuracy	±1%				
	Line Regulation	±1%				
	Load Regulation	±3%				
Input	Voltage Range (V)	110 /220VAC Optional according to switch				
	Frequency Range (Hz)	47~63Hz				
	AC Current (A)	2.1/1.00A 110/220VAC				
	Efficiency (Typ)	≥83%				
Protection	Overload Protection	110 ~ 150% rated output power Protection type: hiccup,automatic restoration after abnormality remove				
	short circuit protection	Protection type: restart to open the power supply and automatic restoration after output short circuit is removed				
Environment	Working Temp	-10~+40°C				
	Working Humidity	20 ~ 90% RH, non-condensing				
	Storage Temp& Humidity	-20°C ~ 85°C;10~95%RH				
	Vibration resistance	10~500Hz,2G per 1min,X、Y、Z axis for each 60 minutes				
Others	MTBF	≥316.2K Hrs,MIL-HDBK-217F(25°C)				
	Dimensions	198*98*42mm (L*W*H)				
	Weight	0.425kg				