

Features

- ◆ Very compact metal cased power supply
- ◆ Universal input AC input,full range
- ◆ Natural air cool
- ◆ Screw terminal block
- ◆ 2 years product warranty
- ◆ Protection: short-circuit, overload,overcurrent and over heat



12V 60W Normal Single output

Specifications

Output	DC Voltage (V)	12V					
	Voltage Range	11.40-12.60V					
	Rated Current (A)	5A					
	Current Range (A)	0 - 5A					
	Rated Power (W)	60W					
	Ripple & Noise (Mvp-p)	120mVP-P					
	voltage accuracy	±1%					
	Line Regulation	±1%					
	Load Regulation	±1%					
Input	Voltage Range (V)	AC110~220V					
	Frequency Range (Hz)	50~60Hz					
	AC Current (A)	1.1~0.55A/110~220VAC					
	Efficiency (Typ)	85%					
Protection	Overload Protection	110 ~ 150% rated output power Protection type: hiccup,automatic restoration after abnormity remove					
	short circuit protection	Protection type: restart to open the power supply and automatic restoration after output short circuit is removed					
Environment	Working Temp	-10~+40℃					
	Working Humidity	20 ~ 90% RH, non-condensing					
	Storage Temp& Humidity	-20℃ ~ 85℃;10~95%RH					
	Vibration resistance	10~500Hz,2G per 1min,X、Y、Z axis for each 60 minutes					
Others	Dimensions	110*78*36mm (L*W*H)					
	Weight	0.23kg					