

Features

- ◆ Very compact plastic case power supply
- ◆ Universal input AC input,full range
- ◆ Natural air cool
- ◆ Screw terminal block
- ◆ 1 year product warranty
- ◆ Protection: short-circuit,Over current and Over Voltage



12V 120W power adapter

Specifications

Output	DC Voltage (V)	12V					
	Voltage Range	11.52V-12.48V					
	Rated Current (A)	10A					
	Current Range (A)	0 - 10A					
	Rated Power (W)	120W					
	Ripple & Noise (Mvp-p)	< 120m Vp-p					
	voltage accuracy	+/- 1%					
	Line Regulation	+/- 1%					
	Load Regulation	+/- 2%					
Input	Voltage Range (V)	AC100-240V					
	Frequency Range (Hz)	47~63Hz					
	AC Current (A)	2~1.3A/100~240VAC					
	Efficiency (Typ)	83%					
AC/DC cable	Length	AC cable-1.2meter,DC cable-1meter					
Tip	Size	5.5*2.1mm					
Protection	Over Voltage Protection	Protection type:The power supply will be auto recovered when over current faults remove					
	Over current Protection						
	Short Circuit Protection						
Environment	Working Environment Temp	0--40°C					
	Working Humidity	0 ~ 95% RH, non-condensing					
	Storage Temp& Humidity	-20 °C ~ 85 °C ;0~95%RH					
	Vibration resistance	Axes,10 cycles per axis					
Others	Dimensions	168*65*39mm (L*W*H)					
	Weight	0.5kg					