

Features

- ◆ Very compact plastic case power supply
- ◆ Universal input AC input,full range
- ◆ Natural air cool
- ◆ Screw terminal block
- ◆ 1 year product warranty
- ◆ Protection: short-circuit,Over current and Over Voltage



12V 72W power adapter

Specifications

Output	DC Voltage (V)	12V				
	Voltage Range	11.52V-12.48V				
	Rated Current (A)	6A				
	Current Range (A)	0 - 6A				
	Rated Power (W)	72W				
	Ripple & Noise (Mvp-p)	< 100m Vp-p				
	voltage accuracy	+/- 1%				
	Line Regulation	+/- 1%				
	Load Regulation	+/- 3%				
Input	Voltage Range (V)	AC100-240V				
	Frequency Range (Hz)	47~63Hz				
	AC Current (A)	1.3~0.85A/100~240VAC				
	Efficiency (Typ)	83%				
AC/DC cable	Length	AC cable-1.2meter,DC cable-1meter				
Tip	Size	5.5*2.1mm				
Protection	Over Voltage Protection	Protection type:The power supply will be auto recovered when over current faults remove				
	Over current Protection					
	Short Circuit Protection					
Environment	Working Environment Temp	0--40°C				
	Working Humidity	0 ~ 95% RH, non-condensing				
	Storage Temp& Humidity	-20 °C ~ 85 °C ;0~95%RH				
	Vibration resistance	Axes,10 cycles per axis				
Others	Dimensions	131*55*30mm (L*W*H)				
	Weight	0.3kg				